



•**FSA386:**
16 DIENTES, COPAS CON Ø EXTERNO DE 48.5MM
/ FSA MEGA EVO
16 DIENTES, COPAS CON Ø EXTERNO DE 49.3MM
/ WHEELS MFG PF30



•**DUB16T: 12 DIENTES, COPAS CON
Ø EXTERNO DE 46MM**
SRAM® BSA DUB®, Race Face® Cinch®
Rotor® BSA30, Zipp® Vuma™
Hawk Racing® BB3086™ y otros.

•**BB9100: 16 DIENTES, COPAS CON
Ø EXTERNO DE 39MM**
Shimano® XTR® BB93
Shimano® Dura-Ace® BB9000
Token®



•**Hollowtech(44mm): 16 DIENTES, COPAS CON
Ø EXTERNO DE 44MM**
· Shimano® SM-BB4600, BB51, BB52, BB5700,
BB-RS500, BB6700, BB70, BB7900 y BB80
· También es compatible con sistemas roscados
externos anteriores: Campagnolo®, Chris King®, FSA®,
MegaExo®, Hope®, SRAM®/Truvativ® GXP®, Race
Face® X-type, Surly®, Wheels®, Rotor® BSA30,
Enduro® TorqTite® BSA86/92/30 y otros.
· Bafang® BB5H, BBS02 (sistemas de motor central con
anillos de bloqueo internos y externos)

•**BBR60: 16 DIENTES, COPAS CON
Ø EXTERNO DE 41MM**
Shimano® Ultegra® BBR60
Shimano® Deore XT® MT-800



LLAVE DE
TORQUE DE 1/2"

